

D7/D8/D9

- ANALOGUE AND DIGITAL ACQUISITION MODULES
- ANALOGUE UNIVERSAL TRANSMITTER WITH ALARMS
- RS485

FEATURES



INPUTS	D7	D9	D8
Number of inputs	1	2	--
Input configuration	Thermocouples: L/J/E (0... +600°C / 32... +1112°F), T (-200...+400°C / -328...+752°F), K/N (0...+1200°C / 32...+2192°F), S/R (0... +1600°C / 32...2912°F), B (0... 1800°C / 32... 3272°F), Ni-NiMo (0... 1100°C / 32... 2012°F), W3, W5 (0... 2000°C / 32... 3632°F) Thermoresistances: PT100 (-99.9... 300.0°C / -99.9... 572.0°F and -200... 600°C / -328... 1112°F) Linear signals: 0/10...50 mV; 0/4...20 mA (shunt) Infrared sensors or programmable on special ranges (custom)		--
Accuracy	0.25% ±1 digit (thermoelements); 0.1% ±1 digit (mA and mV)		--
Digital inputs	1 voltage digital input	1 voltage digital input (+ 2 configurables)	6 digital inputs in voltage or for free voltage contacts, in 2 groups optoisolated (1 and 2 in Hz)
OUTPUTS			
Outputs OUT1-OUT2	OUT1 and OUT2: Relay NO, 2A res./250Vac (4A res./120Vac) / SSR, 1A res./250Vac	OUT1 and OUT2: Relay NO, 2A res./250Vac (4A res./120Vac)/SSR, 1A res./250Vac, logic 0/5 Vdc, not insulated	
Outputs OUT3-OUT4	--	OUT3 and OUT4: logic 0/5 Vdc, not insulated	--
Output OUT5	OUT5: 0/4... 20 mA, 15V max.	--	--
Outputs functions	--	NOT	NOT, PWM, Hold
Auxiliary supply	+24dc, ±20%, 30 mA max. - to supply an external transmitter	--	--
Outputs configuration	Up to 3 alarms	Up to 4 alarms	--
Alarm functions	Sensor break, Latching/Blocking, Loop break, Heater break associated to the timer (if available)		--
FUNCTIONAL			
Setpoint	Reference value	Reference value	--
Special functions (optionals)	--	--	NOT, Toggle, Flip-Flop
Front indication LEDs	3 red (DO) + 1 green (PWR/COM)	4 red (DO) + 1 green (PWR/COM)	6 yellow (DI), 2 red (DO), 1 green (PWR/COM)
Unit of measurement	°C/°F or engineering units (-999... 9999)		--
Signal retransmission	Measure or setpoint retransmission (reference value)	--	--
Serial communication	Isolated RS485 with Modbus RTU protocol		
Baud rate	RS 485 (MASTER or SLAVE) 1200, 2400, 4800, 9600 bit/s 3 wires		
Parameters access	Through serial line and supervision software		
GENERAL			
Power supply	24Vac (-25...+12%), 24Vdc (-15...+25%) (50/60Hz)		
Power consumption	4 VA max.	5 VA max.	4 VA max.
Dimensions	22.5 x 99, depth 114.5 mm		
Weight	155 g approx.	156 g approx.	152 g approx.
Connections	PWS and COM: 0.08... 1.5 mm ² (AWG28-AWG16) Inputs/Outputs: 0.2... 2.5 mm ² (AWG24 - AWG12)		
Mounting	On OMEGA DIN A rail		
Protection degree	IP20 (terminal block)		
Operating / storage temperature	0... 50°C (32... 122°F)/-30... 70°C (-22... 158°F)		
Operating humidity	5... 95 RH% without condensation		
Conformity	EN61010-1 (IEC1010-1)		


Note: these modules can be inserted into Profibus DP and DeviceNet nets, together with a DX module, with the possibility of automatic reconfiguration.

HOW TO ORDER

To compose the part number, pls. choose one of the option for each variable

D7/D8/D9	CODE
POWER SUPPLY	
24 Vac/Vdc	5
OUT 1 AND OUT 2	
Relay (D7 only)	0
Relay-Relay	1
Relay-Logic (D8 and D9 only)	2
Logic-Logic (D8 and D9 only)	3
Triac-triac (D8 and D9 only)	4
Triac-Logic (D8 and D9 only)	5
SERIAL COMMUNICATION	
RS485	5
OPTION 1	
Not available	0
Continuous output (D7 only)	5
SPECIAL FUNCTIONS	
Not available	0
INSTRUCTION MANUAL	
Italian / English	0
Not available	9
OPTION 2	
Shunt 1% (D7 and D9 only)	0
Shunt 0.1% (D7 and D9 only)	2
OPTION 3	
Not available	0
Conformal coating	3

DIMENSIONS



CONNECTIONS

